



ITEM NO.	QTY	PART NAME	A-205		A-207		A-207-MO	
			MATERIAL	PART NO.	MATERIAL	PART NO.	MATERIAL	PART NO.
1	1	BODY	STEEL	205-1-CS	STAINLESS	207-1-SS	CF8M STAINLESS	207-1-MO
2	1	SPRING	STAINLESS	207-2-MO	STAINLESS	207-2-MO	316 STAINLESS	207-2-MO
3	1	SPRING SEAT	STAINLESS	207-3-SS	STAINLESS	207-3-SS	STAINLESS	207-3-SS
4	1	LOCK NUT	STEEL	205-4-CS	STAINLESS	207-4-SS	316 STAINLESS	207-4-SS
5	1	STEM	STAINLESS	207-52-SS	STAINLESS	207-52-SS	316 STAINLESS	207-52-MO
6	1	PRESSURE SEAL	BUNA-N <sup>(1)</sup>	205-6-BN	BUNA-N <sup>(1)</sup>	205-6-BN	BUNA-N <sup>(1)</sup>	205-6-BN

NOTE: 1 Alternate material available

Standard minimum start to discharge pressure setting is 0.75 PSI vacuum.  
Alternate start to discharge pressure settings are available.

Net flow area: 1.12 square inches