



ITEM NO.	QTY.	PART NAME	MATERIAL	A-209-S		A-209-WS	
				QTY.	PART NO.	QTY.	PART NO.
1	1	BODY ⁽¹⁾	STAINLESS	1	209-12-SS	1	209-12-SS
2	1	SPRING	STAINLESS	1	205-2-MO	1	205-2-MO
3	1	SPRING SEAT	STAINLESS	1	207-3-SS	1	207-3-SS
4	1	LOCK NUT	STAINLESS	1	207-4-SS	3	207-4-SS
5	1	STEM ⁽¹⁾	STAINLESS	1	207-52-SS	1	207-53-SS
6	1	PRESSURE SEAL	BUNA N 70 D	1	205-6-BN	1	205-6-BN
7	1	WEATHER CAP	STAINLESS	----	-----	1	205-7-SS
8	1	RETAINER RING	STAINLESS	1	207-8-SS	1	207-8-SS
9	1	SCREEN ASSEMBLY	STAINLESS	1	209-9-SS	1	209-9-SS
10	1	NAMEPLATE	STAINLESS	1	209-87-SS	1	209-87-SS

NOTE: 1 Passivated

Standard minimum start to discharge pressure setting is 0.75 PSI vacuum.
Alternate start to discharge pressure settings are available.

Net flow area: 1.12 square inches