



ITEM NO.	QTY.	PART NAME	A-209-W-NS		A-209-W-NS-MO	
			MATERIAL	PART NO.	MATERIAL	PART NO.
1	1	BODY	STAINLESS	209-14-SS	STAINLESS	209-14-MO
2	1	SPRING	STAINLESS	207-2-MO	STAINLESS	207-2-MO
3	1	SPRING SEAT	STAINLESS	207-3-SS	STAINLESS	207-3-SS
4	1	LOCKNUT	STAINLESS	207-4-SS	STAINLESS	207-41-SS
5	1	STEM ASM	STAINLESS	207-52-SS	STAINLESS	207-52-MO
6	1	PRESSURE SEAL	BUNA N (1)	205-6-BN	BUNA N (1)	205-6-BN
7	1	WEATHER CAP ASM	STAINLESS	209-7-SS	STAINLESS	209-7-SS
8	1	NAMEPLATE	STAINLESS	209-88-SS	STAINLESS	209-88-SS
9	3	CAP SCREW	STAINLESS	208-9-SS	STAINLESS	208-9-SS

NOTES :

- (1) ALTERNATE MATERIAL AVAILABLE.
- (2) STANDARD MINIMUM START TO DISCHARGE PRESSURE SETTING IS 0.75 PSI VACUUM. ALTERNATE START TO DISCHARGE PRESSURE SETTINGS ARE AVAILABLE.

NET FLOW AREA: 1.12 SQUARE INCHES.

VACUUM RELIEF VALVES

A-209-W-NS, A-209-NS-MO

2-1/2 NPT - NO STEP VACUUM RELIEF VALVES

© 2002 Midland Manufacturing Corp.
All designs subject to change without notice. Installation dimensions and mounting arrangements are for general information. Certified drawings are available upon request.