



ITEM NO.	QTY.	PART NAME	A-215-W-NS		A-217-W-NS	
			MATERIAL	PART NO.	MATERIAL	PART NO.
1	1	BODY	STEEL	215-100-CS	STAINLESS	217-100-SS
2	1	SPRING	STAINLESS	SEE TABLE	STAINLESS	SEE TABLE
3	1	SPRING SEAT	STAINLESS	217-3-SS	STAINLESS	217-3-SS
4	1	LOCK NUT	STEEL	215-44-CS	STAINLESS	217-4-SS
5	1	STEM	STAINLESS	217-50-SS	STAINLESS	217-50-SS
6	1	PRESSURE SEAL	BUNA-N ⁽¹⁾	215-6-BN	BUNA-N ⁽¹⁾	215-6-BN
7	1	WEATHER CAP	STAINLESS	215-70-SS	STAINLESS	215-70-SS
8	1	NAMEPLATE	STAINLESS	217-84-SS	STAINLESS	217-84-SS
9	2	POST	STAINLESS	217-90-SS	STAINLESS	217-90-SS
10	2	LOCKNUT	STAINLESS	720-181-SS	STAINLESS	720-181-SS

NOTE: 1 Alternate material available.

-Standard minimum start to discharge pressure setting is .75 PSI vacuum.

-Alternate vacuum settings are shown in table.

-Net flow area 0.71 sq. in.

VACUUM SETTING (PSI)	SPRING P/N
.75	215-2-MO
3	215-27-MO
4	215-23-MO
5-8	215-24-MO
10	215-25-MO

VACUUM RELIEF VALVES NO STEP VACUUM RELIEF VALVE

A-215-W-NS, A-217-W-NS