



ITEM NO.	QTY.	PART NAME	A-430-T		A-432-T		A-434-T	
			MATERIAL	PART NO.	MATERIAL	PART NO.	MATERIAL	PART NO.
1	1	TOP	MALL. IRON	425-1-MI	MALL. IRON	425-1-MI	STAINLESS	429-1-SS
2	1	BASE	STEEL	435-2-CS	STAINLESS	435-2-SS	STAINLESS	435-2-SS
3	1	DISC ⁽²⁾	STAINLESS	425-3-SS	STAINLESS	425-3-SS	STAINLESS	425-3-SS
4	1	RETAINER	DUCTILE IRON	425-4-DI	DUCTILE IRON	425-4-DI	STAINLESS	429-4-SS
5	1	SWING PIN	SS/STEEL	425-5-XS	SS/STEEL	425-5-XS	STAINLESS	429-5-SS
6	4	NUT	STEEL	425-6-CS	STEEL ⁽¹⁾	425-6-CS	STAINLESS	429-6-SS
7	3	STUD	STEEL	425-7-CS	STEEL ⁽¹⁾	425-7-CS	STAINLESS	429-7-SS
8	1	HINGE PIN	STEEL	425-8-CS	STEEL ⁽¹⁾	425-8-CS	STAINLESS	429-8-SS
9	1	EYE BOLT PIN	STEEL	425-9-CS	STEEL	425-9-CS	STAINLESS	434-9-SS
10	1	CHAIN	STEEL	24-3-CS	STEEL	24-3-CS	STEEL ⁽¹⁾	24-3-CS
11	4	COTTER PIN	STAINLESS	545-28-SS	STAINLESS	545-28-SS	STAINLESS	545-28-SS
12	1	EYE BOLT	STEEL	425-12-CS	STEEL ⁽¹⁾	425-12-CS	STAINLESS	429-12-SS
13	1	SEAL ⁽²⁾	SS/LEAD	425-13-XS	SS/LEAD	425-13-XS	SS/LEAD	425-13-XS
14	1	TANK CHAIN ⁽²⁾	STEEL	425-14-CS	STEEL ⁽¹⁾	425-14-CS	STEEL ⁽¹⁾	425-14-CS
15	2	SCREW/RIVET	STAINLESS	763-11-SS	STAINLESS	763-11-SS	STAINLESS	424-15-SS
16	1	NAMEPLATE	STAINLESS	424-16-SS	STAINLESS	424-16-SS	STAINLESS	424-16-SS

NOTE: 1 Alternate material available. 2 Not furnished unless requested.

FLOW CAPACITY WITHOUT RUPTURE DISC INSTALLED	
TANK PRESSURE (PSIG)	FLOW RATE (SCFM)
85	3332

RUPTURE DISC DEVICES

A-430-T, A-432-T, A-434-T

2" DISC HOLDER WITH BAFFLE TRIANGULAR BASE